


Feb.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- NOTES
1. APPLICABLE WIRE IS AWG #17~#22. (UL1007 : AWG #18~#22)  
INSURATION DIAMETER φ 2.25mm MAX.
  2. PER REEL : 6000 CONTACTS.
  3. APPLICABLE CRIMPING MACHINE AND CRIMPING CONDITIONS  
WILL BE SPECIFIED ACCORDING TO AWG# OR WIRE APPLIED.
  4. REFER TO ETAD-E2961 FOR INCORPORABLE CONNECTOR PARTS AND APPLICABLE CONNECTOR.
  5. REFER TO ATAD-E3238 FOR CRIMP QUALITY STANDARDS.

NO.		MATERIAL		FINISH . REMARKS		NO.		MATERIAL		FINISH . REMARKS	
		1		COPPER ALLOY				CONTACT AREA : GOLD PLATING 0.2μm min		TERMINAL AREA : TIN PLATING 1μm min	
				UNDER : NICKEL PLATING 0.5μm min							
UNITS		SCALE		COUNT		DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	
mm		5 : 1		△						DATE	
<b>HRS</b> HIROSE ELECTRIC CO., LTD.		APPROVED : MN. KENJO		20211222		DRAWING NO.		EDC-397156-00-00			
		CHECKED : KG. OKITA		20211221		PART NO.		PQ50S2-1822SCFA			
		DESIGNED : HY. MATSUDA		20211221		CODE NO.		CL0236-0036-0-00			
		DRAWN : HY. MATSUDA		20211221				1/1			