ES EPG 45 DIN 70

Crimping tools for cable lugs, connectors and wire-end ferrules with interchangeable inserts

- extremely fast processing thanks to hydraulic support
- large processing range up to 300 mm²
- 270° revolving quick-action crimping head
- automatic pressure limitation and monitoring via pressure sensor
- electronic control and monitoring of the crimping process
- Saving of all crimping cycles and error messages to internal memory
- Reading of all cycles and error messages via USB
- Li-ion rechargeable battery with charge status indicator: 18 V, 2 Ah

General ordering data

Version	70mm², Indent crimp
Order No.	1501380000
Type	ES EPG 45 DIN 70
GTIN (EAN)	4050118309744
Qty.	1 pc(s).

Creation date June 14, 2025 3:53:56 PM CEST

Weidmüller ⅀Ξ

ES EPG 45 DIN 70

Technical data

Dimensions and weights

Depth	12 mm		Depth (inches)	0.472 inch
Height	60 mm		Height (inches)	2.362 inch
Width	30 mm		Width (inches)	1.181 inch
Net weight	151 g			

Crimp inserts

Crimp cross-section copper	70		Crimping width	12 mm
Crimping width in mm	12			

Description of contact

Conductor cross-section, max. AWG	2/0		Conductor cross-section, min. AWG	2/0
Crimping range, max.	70 mm²			

tool data crimping

Cable lug cross section	nominal	70 mm²
Crimping type/profile	Indent crimp	

Classifications

ETIM 6.0	EC001282		ETIM 7.0	EC001282
ETIM 8.0	EC001282		ETIM 9.0	EC001282
ETIM 10.0	EC001282		ECLASS 9.0	21-04-90-90
ECLASS 9.1	21-01-90-90		ECLASS 10.0	21-04-90-90
ECLASS 11.0	21-04-90-90		ECLASS 12.0	21-04-90-90
ECLASS 13.0	21-04-90-90		ECLASS 14.0	21-04-90-90
ECLASS 15.0	21-04-90-90			

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Downloads

Catalogues	Catalogues in PDF-format
Brochures	