

Customer Information Sheet

DRAWING No.: S8091-46R

SHEET 2 OF 2



IF IN DOUBT - ASK

©





NOT TO SCALE

THIRD ANGLE PROJECTION


ALL DIMENSIONS IN mm








RECOMMENDED PCB PAD LAYOUT



SECTION Y-Y



SECTION X-X



COMPONENT SPECIFICATION:
MATERIAL: PHOSPHOR BRONZE
FINISH: 3µ 100% TIN OVER 2µ NICKEL
CAPACITY MAX: 2 x Ø0.9mm WIRES
COAX USAGE:
SUITABLE FOR USE AS A COAXIAL BRAID/SCREEN GROUNDING CLIP WITH UL1745-DSB CX-50, RFX50-DS32-132 AND 1.32mm MINI COAXIAL TYPE CABLE (Ø1.12 BRAIDING).

NOTES:
1. QUANTITY OF COMPONENTS PER REEL = 3000.
2. THIS PRODUCT IS TAPED AND REELED IN ACCORDANCE WITH EIA-481 (ELECTRONICS INDUSTRIES ASSOCIATION).

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH:

S/AREA:

mm²

TITLE: SMT CABLE CLIP FOR Ø0.9mm / COAX UL1745-DSB CX-50, RFX50-DS32-132, 1.32mm MINI COAXIAL CABLE GROUNDING CLIP (Ø1.12 BRAIDING) IN TAPE & REEL

DRAWING NUMBER:

S8091-46RSHT
2 OF 2

SF	C	24.06.11	11327
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.FLOWER	
CHECKED:		R.ADDE	
DRAWN:		S.FLOWER	
CUSTOMER REF.:			
ASSEMBLY DRG:			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Harwin:

S8091-46R